

# ACCO® "TN" Tuna Net Chain

## The Best Chain for a Tough Job.

ACCO® uses high quality steel, especially formulated and heat treated for tuna fishing. Every heat treated lot, approximately 3000 lbs. is sampled and destructively tested for material strength and link elongation - assuring compliance to design criteria. All Tuna Net Chain is then proof tested, 100%, every link.

ACCO® Tuna Net Chain is then continuously Hot Dip Galvanized to provide the deep strong protective coating you have come to expect which has over 30% more zinc per unit volume than mechanical coating. In the hot dip process the galvanized zinc coating is alloyed with the base steel creating a METALLURGICAL bond that is several orders of magnitude stronger than mechanical bonding. This zinc-steel bond is immune to further corrosion for the life of the zinc. If the chain's steel base is exposed by cuts or nicks, the base steel will not rust until the nearby zinc is consumed.



### Hot Galvanized Tuna Net Chain

Trade Size	Wire Dia. Inches	WLL Lbs.	Inside Length	Inside Width	Wt. Per Drum Lbs.	Ft. Per Steel Drum	Hot Galvanized Stock No.
3/8"	0.394	6,600	1.33"	0.57"	620	400	520140692
7/16"	0.464	8,750	1.37"	0.75"	687	300	520140792
1/2"	0.519	11,300	1.72"	0.75"	541	200	520140892
9/16"	0.551	12,150	1.70"	0.85"	627	200	520140992
5/8"	0.630	15,800	1.93"	0.91"	605	150	520141092
3/4"	0.750	24,700	2.42"	1.13"	572	100	520141292



**PEERLESS**  
INDUSTRIAL GROUP

Your Link to Quality, Strength, and Service Since 1917.

### Export Office

Peerless Chain Company  
45 High Point Ave.  
Portsmouth, RI 02871 (USA)  
Tel (001)-401-683-2900  
Fax (001)-401-683-0775  
Steve@Chainusa.com

# ACCO® Trawl Chain Grade 100



## Short Link

Reference No.	Diam MM	Inside Link Dimensions MM		Weight Kgs/Mtr	Breaking Load Metric Tons	Standard Length - Mtrs
		Inside Length	Inside Width			
TSL10-10	10	30	14	2.2	15.5	200
TSL13-10	13	39	18.1	3.6	26.5	150
TSL16-10	16	48	22.4	5.5	41	110
TSL19-10	19	60	29	7.8	57	75



## Medium Link

Reference No.	Diam MM	Inside Link Dimensions MM		Weight Kgs/Mtr	Breaking Load Metric Tons	Standard Length - Mtrs
		Inside Length	Inside Width			
TML10-10	10	40	16.5	1.88	15.5	200
TML13-10	13	52	22	3.2	26.5	150
TML16-10	16	64	24	4.9	41	110
TML19-10	19	76	29	7	57	75
TML22-10	22	86	27	9.4	85	60



## Long Link

Reference No.	Diam MM	Inside Link Dimensions MM		Weight Kgs/Mtr	Breaking Load Metric Tons	Standard Length - Mtrs
		Inside Length	Inside Width			
TLL13-10	13	80	22	2.85	26.5	150
TLL16-10	16	100	26	4.35	40	100
TLL19-10	19	100	28	6.35	57	75
TLL22-10	22	120	37	8.8	75	70

- High strength special steels, hardened and tempered, resistance to shock loading and wear
- Packing - steel drums (Pallet boxes available on request)
- Surface finish - Peer Blue

### Corporate Office

Peerless Chain Company  
1416 East Sanborn Street  
Winona, MN 55987 (USA)  
[www.peerlesschain.com](http://www.peerlesschain.com)

### Export Office

Peerless Chain Company  
45 High Point Ave.  
Portsmouth, RI 02871 (USA)  
Tel (001)-401-683-2900  
Fax (001)-401-683-0775  
[Steve@Chainusa.com](mailto:Steve@Chainusa.com)