



**Peerless Trailer Safety Chains** meet the requirements of SAE standard J684 for trailer couplings, hitches, and safety chains used in conjunction with all types of trailers or towed vehicles whose Gross Vehicle Weight Rating (GVWR) does not exceed 4540 kg (10,000 lbs). Safety Chains are the system (linked chains and attachment means, or other) that provide a secondary means of connection from the rear of the towing vehicle to the front of the trailer. The Safety Chain's mission is to retain the connection between the towing vehicle and trailer in the event of a ball or coupler failure, ensuring the vehicle can still safely maintain control and guide the trailer to a safe stopping point.

PLEASE NOTE: It should not be interpreted that safety chains can ensure that vehicle control or connection will be maintained in the event of vehicle incidents such as loss of control, rollover, jack knife, collision, etc.



## CLASS 1 TRAILER SAFETY CHAINS

Class 1 Utility Trailer Chains								
Stock #	Trade Size	Length	Hooks	Qty Per	Lbs. Per	GV	WR	
Zinc	(Inches)	(Inches)	поокз	Drum	Drum	(Lbs.)	(Kgs.)	
6800004	3/16" G30	27"	1 (w/latch)	250	267	2,000	910	
6800031		48"	2 (w/latch)	100	192			
8650130		48"	2 (no latch)	100	176			

## CLASS 2 TRAILER SAFETY CHAINS

Class 2 Utility Trailer Chains								
Stock #	Trade Size	Length	Hooks	Qty Per	Lbs. Per	GVWR		
Zinc	(Inches)	(Inches)	поокѕ	Drum	Drum	(Lbs.)	(Kgs.)	
6800043	5/0	24"	1 (w/latch)	200	252	3,500	1,600	
*8611029		27"	1 (w/latch)	500	684			
*8611559		40"	1 (w/latch)	50	93			

\*HDG Finish

## TRAILER SAFETY CHAINS





	Class 3 Utility Trailer Chains							
Stock #	Trade Size	Length	th Hooks Qty Per Lbs. Per	Lbs. Per	GVWR			
Zinc	(Inches)	(Inches)	HOOKS	Drum	Drum	(Lbs.)	(Kgs.)	
8640210		24"	1 (no latch)	150	227	5,000	2,270	
8671115		30"	1 (no latch)	100	190			
8666230	1/4" G30	48"	2 (no latch)	100	307			
8650240		60"	2 (no latch)	50	375			
8666250		72"	2 (no latch)	50	225			
6840215		30"	1 (w/latch)	100	185			
8607867		36"	1 (w/latch)	250	497			
6800032		48"	2 (w/latch)	100	300			
6800033		60"	2 (w/ latch)	100	360			
8610956		72"	2 (w/latch)	50	208			
8612325	5/16"G30	60"	2 (w/ latch)	100	459	5,000	2,270	
8607280	5/16" G30	30"	1 (w/latch)	75	193	5,000	2,270	

## CLASS 4 & ABOVE TRAILER SAFETY CHAINS

Class 4 & above Utility Trailer Chains							
Stock#	Trade Size	Length	Hooks	Qty Per	Lbs. Per	GV	WR
Zinc	(Inches)	(Inches)	поокз	Drum	Drum	(Lbs.)	(Kgs.)
8607006		30"	1 (no latch)	100	300	7,600	3,447
6800041	8/0 (0.342)	30"	1 (w/latch)	100	257		
6807902	0/0 (0.342)	34"	1 (w/latch)	100	300		
6800006		36"	1 (w/latch)	50	179		
8607903	5/16" G30	36"		100	310		
*6800025	1/4" G70	28"		275	543	12,600	5,714
*6800028		36"	1 Clevis Slip	250	590		
*8605734	3/8"G43	36"	Hook & Latch	50	250	16,200	7,348
*6800026	3/8" G70	36"		100	515	26,400	11,975
*8607894	1/2"G70	40"		30	301	45,200	20,500
*8610004	1/2"G80	40"	Clevis Sling	25	335	48,000	21,770
*8610005	5/8"G80	40"	Hook & Latch	25	455	72,400	32,840
AND COLORS OF THE COLORS OF TH							

<sup>\*</sup> Not Defined per SAE J684, chain & attachments are manufactured & tested per NACM &/or ASTM standards.

PROUD MEMBERS OF THE FOLLOWING ASSOCIATIONS:









800.873.1916 WWW.PEERLESSCHAIN.COM